

Primary Calibrators



Personal sampling pumps are key tools for exposure assessment. The accuracy of sampling depends on how much air passes through the sampling media and good laboratory analysis. As a common practice, sampling pumps should be calibrated before and rechecked after sampling using a calibration device.

TSI offers two Primary Calibrator models for calibrating pumps or any other air sampling instrument that draws an active air sample. These small, portable, battery-operated units are lightweight and easy to use. Volumetric flowrate is displayed continuously, making pump adjustment, calibration and periodic flow checks fast and easy in real-time. These Primary Calibrators are temperature-compensated and pressure-corrected to calculate volumetric flow rate at an accuracy within 2% of reading.

Primary calibrator kits are available complete with a soft-sided carrying case, battery pack, tubing, user guide and NIST-traceable calibration certificate.

Specifications

Flow Measurement Range

Model 4146	0.01 to 20 lpm
Model 4046	2.5 to 300 lpm

Accuracy

Model 4146	±2% or 0.005 std. lpm, whichever is greater
Model 4046	±2% or 0.05 std. lpm, whichever is greater

Dimensions

Model 4146	5 in. x 2 in. x 1.25 in. (12.7 cm x 5 cm x 3.2 cm)
Model 4046	7.2 in. x 2.5 in. x 2.1 in. (18.3 cm x 6.4 cm x 5.3 cm)

Shipping Weight

Model 4146	2.2 lbs (1.0 kg)
Model 4046	3.0 lbs (1.1 kg)

Warm-up Time

1 min

DC Power Input

7.5 VDC ±1.5 V, 300 mA max

Specifications are subject to change without notice.



TSI Incorporated

Corporate Headquarters—Tel: 651 490 2811 **Toll Free:** 1 800 874 2811 **Fax:** 651 490 3824 **E-mail:** answers@tsi.com
Contact TSI or visit www.tsi.com for information on specific office locations worldwide.

For current information
www.tsi.com

